



AUX GROUP



@AUXGROUP1

Official Accounts

NINGBO AUX IMP.&EXP.COLTD.

Add: No. 1517, East Section of Yincheng Avenue, Jiangshan,  
Yinzhou, Ningbo, Zhejiang, P. R. China  
Tel: +86-574-88220564

**AUX**  
**MOROCCO**  
**PRODUCT CATALOGUE**

# GROUP PROFILE

1 Established in 1986, AUX Group is an enterprise group which covers several industries: home appliances, electrical equipment, medical service, real estate and investment. For many years it ranked China's top 500 enterprises.

2 In 2021, the group sales reaches RMB 72 billion, with total assets of RMB 64.7 billion. It has over 30,000 employees, and 11 manufacturing bases in Ningbo(3), Nanchang, Tianjin, Ma'anshan, Zhengzhou, Brazil, Indonesia, Thailand and Poland, 6 R&D centers. AUX is a leading producer of Smart Meter and Power Box in its sector, and has also ranked No.3 in the Air-Conditioner industry in 2018-2021. Currently, it has invested and operated 35 medical institutions.

3 It owns 2 listed companies (601567.SH, 02080.HK). As a National-Recognized Enterprise Technology Center, a Technology Innovation Model Enterprise, National Intellectual Property Demonstration Enterprise and a National Post-doctoral Work station, it owns two globally famous brands: AUX and Sanxing, which worth over RMB 41 billion.

4 When AUX is working on its development, it also cares about performing its social responsibilities. In the past years, it has donated RMB 309 million in total to various public programs, such as the field of targeted poverty alleviation, education, disaster relief and environment protection.

5 In the new era, aiming to become a world-class enterprise, AUX will keep carrying out the mission of "Creating an intelligent living environment and Cultivating great talents" and work hard to achieve the strategic goal of "100 billion market value, 100 billion sales and 10 billion profits".

## INTELLIGENT MANUFACTURING

Industries covering home appliances, electrical equipment, medical service, real estate and investment, etc.

In 2022, group revenue Of RMB 81 billion, over 30,000 employees


Public welfare donation RMB 309 million  
NEEDED

11 Manufacturing Bases

6 R&D Centers



Exported to 123 countries and regions , over 400 cooperative customers



## AWARDS



Leading Comfortable & Healthy Brand

Innovation Excellent Case Award



IF DESIGN AWARD



AWE Excellent Product Award



Quality Benchmark Brand


## HONOR



Demonstration enterprise



Gold award



Pilot enterprise



Vice chairman unit

## CERTIFICATION



CE



EAC



AHRI



ETL



TISI



CB



ESMA



SASO



RoHS



EUROVENT



ISO



ICC

## 1986

Startup from Longguan Town

At the age of 25, Zheng Jianjiang volunteered to contract the Longguan Clock&Watch Parts Factory, which was on the verge of bankruptcy, and started his business.

## 1994

Entered the air-conditioning industry and created AUX brand

With an expansion of 1000 times, AUX made its way to the top 4 in the air-conditioning industry, and ranks third in China's air-conditioning industry.

## 1989

Entered the instrument Industry and founded Sanxing brand later

With an expansion of 500 times, we claimed the crown of power meters nationwide, and are now a leading integrated solution provider of intelligent power distribution.

## 2006

Ningbo Mingzhou Hospital (later renamed as Zhejiang University Mingzhou Hospital) opened

We started to extend our business into medical industry and became a pioneer of non-governmental hospitals and a cross-industry representative with more than ten years of efforts in the path characterized by private-capital hospital running.

## 2000

Entered the real estate industry

We have our network cover more than ten cities and are now a comprehensive land agent of diversified business models.

## 2009

Entered the investment industry

We established Huijin Micro-credit Company and jointly held shares in 2 banks.

## 2011

Sanxing Electric (601567)

It was listed in the main board of Shanghai Stock Exchange and was later renamed as "Sanxing Medical".

## 2012

Set up R&D Center successively in Hangzhou and Ningbo

These promoted the technical research and application of intelligent power grid and intelligent household electrical appliances.

## 2013

Established a financial center in Shanghai

The center carried out financial leasing business.

## 2014

Set up a medical group

It comprehensively deployed the healthcare strategy.

## 2015

Established overseas factories in Brazil and Indonesia

It worked in overseas real estate development in Australia and was renamed as AUX International after merger with Hong Kong stocks (02080.HK).

## 2017

Newly built the intelligent household air conditioning industrial park in Ma'anshan

We advanced towards kitchen appliance industry together with the expansion of hospitals and medical healthcare.

## 2019

Initiating in the industry

It initiated the mode of "Internet direct selling of air conditioners". The Thailand Base was officially completed in August.

## 2016

Leaped to No. 3 in air conditioner production scale

We newly built a production base for the export of intelligent household electrical appliances.

## 2018

Launched Strategy X to build intelligent household appliance production bases in Thailand and Zhengzhou

We aimed to build the R&D Center in Japan into a global R&D highland for household electrical appliances.

**STARTUP & DEVELOPMENT (1986-2019)**

# 2020-PRESENT

Facing the new era,  
AUX adheres to the corporate mission of "creating intelligent life and  
cultivating outstanding talents" and aspires to become a world-famous enterprise.




Responsibility



Quality



Forging ahead



Innovation



## April 2020

Commendation meeting of the pioneer  
in aiding Hubei of AUX Group



## Leading meeting



## June 2020

Cloud conference of the air conditioner  
with removable and washable  
movement of AUX Group

## December 2020

Roundtable seminar on "Innovation  
boosts high-quality development of  
manufacturing industry"



## Official cooperation

## February 2021

Official exclusive supplier of air  
conditioner for the 19th Asian Games  
Hangzhou 2022



## High-end image

## July 2023

China (Ningbo) International Appliance  
Expo



## Brilliant at the exhibition

## October 2023

The 134th China Import and Export Fair  
(Canton Fair)



## Secure quality

## November 2022

China polar scientific research partner



## Forging ahead with determination

## September 2023

Ranked among the top 500 Chinese  
enterprises in 2023



## Powerful combination

## November 2023

Cooperation with Panasonic in the  
compressor field

# MOROCCO CATALOGUE

## C-SERIES

Series	Appearance	Refrigerant	Type	09K	12K	18K	24K	30K
C-SERIES		R410A	50HZ	●	●		●	

## C+PRO-SERIES

Series	Appearance	Refrigerant	Type	09K	12K	18K	24K	30K
C+Pro-SERIES		R410A	50HZ	●	●			

## Q-SERIES

Series	Appearance	Refrigerant	Type	09K	12K	18K	24K	36K
Q-SERIES		R410A	50HZ	●	●	●	●	●

## F-SERIES

Series	Appearance	Refrigerant	Type	09K	12K	18K	24K	30K
F-SERIES		R410A	50HZ	●	●	●	●	●

## PORTABLE

Series	Appearance	Refrigerant	07K	08K	12K	14K
Portable-MF		R410A		●		

# CONTENTS



## 1 Wall mounted

C-seires	P01-08
C+PRO-seires	P09-14
Q-seires	P15-20
F-seires	P21-26


## 2 Portable

Portable-MF	P27-30
-------------	--------

# C-SERIES



Size:mm(12k)



▼ OUTDOOR UNIT




▼ REMOTE CONTROLLER

## APPEARANCE




## C-SERIES BASIC



## PANEL SELECTION





Originating from the craftsmanship of Japanese design, it uses the golden ratio of the Pythagorean Theorem to create a minimalist texture body, interpreting a new home aesthetics

## MAIN SELLING POINT

### LARGE COOLING CAPACITY

Air outlet: Wider and further, faster cooling and heating  
 Air supply mode: Wide-angle air supply with large outlet brings the wind across the living room and dining room, providing a comfortable environment



### WIFI CONTROL

Develop the leading technology and intelligently connect with mobile phone, achieving remote control of the air conditioner



### SMART MICRO-PERFORATION WIND

Equipped with new micro-perforation air guide plate delivers lighter, softer, and more comfortable air supply in the guaranteed cool environment



### 8°C CONSTANT TEMPERATURE

Constant temperature heating, surrounded by comfortable breeze



### EASY INSTALLATION

Detachable underjaw and plate support for large operation space. The installation efficiency is greatly improved, saving 20% of installation time



### THE FIFTH GENERATION OF SELF-CLEANING

Comprehensive upgrade, six steps for cleaning indoor and outdoor units thoroughly. Remove four major bacteria with 99.9% sterilization rate



### FULL DC INVERTER COMPRESSOR

Start from -30°C low temperature to 60°C high temperature, not afraid of cold and heat. Low frequency operation and energy saving



CATEGORY	DETAIL	FUNCTION	STANDARD	OPTIONAL
PERFORMANCE	MODE	refrigeration	●	
		heat production	●	
		automation	●	
		Drying/Dehumidifying	●	
		disclose information	●	
		sleep	●	
	RUN	High-temperature refrigeration	●	
		low-temperature heating	●	
		Wide temperature operation	●	
		Wide voltage operation	●	
ENERGY CONSERVATION	COMMON	ECO II	●	
		0.5W standby	●	
HEALTHY	STERILIZATION	Cold plasma		●
		anion		●
		Explosion-proof anion		●
		UV sterilization		●
	SELF-CLEANING	Automatic washing	●	
		High temperature sterilization	●	
	RESISTANCE ROT	Dry and mildew proof	●	
		Mosquito filter	●	
	FILTER	Silver ion filter		●
		Vitamin C anti-mite filter		●
		Germicidal mesh/antibacterial filter		●
		Activated carbon filter		●
		Lysozyme /HEPA filter		●
		Three color sterilization net (red yellow black)		●
		Three color sterilization net (blue, white and green)		●
		Remove PM2.5 filter		●
		Formaldehyde-busting filter		●
COMFORT	WIND CONTROL	No wind (soft wind)		●
		One key wind relief COSY		●
		Cold blast protection	●	
		Mute/mute wind		
		7 speed wind speed (medium high, medium low)	●	
		Remote air supply(7.5m)	●	
		Set up and down the wind	●	
		swing		●
	TEMPERATURE CONTROL	Freeze frame swing wind	●	
		Rapid refrigeration 30s/heating 60s	●	
	SOUND CONTROL	8°C heating/8°C Constant temperature 8°C		●
	LIGHT CONTROL	Mute remote control	●	
		Screen display	●	

# STANDARD/ OPTIONAL

CATEGORY	DETAIL	FUNCTION	STANDARD	OPTIONAL
INTELLIGENT	TEMPERATURE-LIMITED	Temperature range regulation	●	
		Remote temperature limiting	●	
		Switch to ambient temperature	●	
	CONTROLS	°C/°F switchover °C/°F	●	
		USB WiFi	●	
		integration WiFi	●	
	INTIMATE DETAIL	Drive-by controller	●	
		Voice panel/Voice control	●	
		on-off	●	
	RATION POWER	iFavor	●	
		iFeel		●
		ISAVE		
	OTHER	Infant care		
		Child lock	●	
		timing	●	
	RELIABILITY	Blackout memory	●	
		Intelligent power limiting(WIFI)		●
		Remote control power limiting		●
		Intelligent preheating	●	
		Smart defrost	●	
AFTER SALE	ELECTRIC HEATING	Forced defrost	●	
		self-diagnosis	●	
		Filter cleaning reminder	●	
		Electric chassis heating		●
		Auxiliary electric heating		
	OTHER	"Fluorine deficiency protection /Refrigerant leak protection	●	
		"5VA Fire rating of electric control box	●	
		Two corrosion resistant		●
		PCB three anti-paint PCB		●
		Gold fin		●
	DISASSEMBLY AND ASSEMBLY	External shock pad		●
		Removable lower jaw	●	
		"Motherboard easy to disassemble (PCB plug-in)	●	
		Fluorine collection mode		●
		Low temperature refrigeration (-10°C)		●
	DISASSEMBLY AND ASSEMBLY	Easy to install hanging plate		●
		Hanging plate level		●

# PRODUCT SPECIFICATION SHEET


AUX SPLIT ROOM AIR CONDITIONER			NUMBER	09K	12K
Items				ASW-H09B7A4/CAR3DI	ASW-H12C5A4/CAR3DI
Nameplate Parameter	Rated Capacity	Cooling	W	2700 (600-4000)	3600 (800-4100)
		Cooling	BTU	9000	12000
		Heating	W	3200 (800-4200)	3800 (1000-4200)
		Heating	BTU	9000	12000
	Rated Power Consumption	Cooling	W	780 (100-1200)	1120(100-1600)
		Heating	W	840 (200-1200)	1050(300-1600)
	Rated Running Current	Cooling	A	3.7(0.56-5.32)	5.30(0.7-7.8)
		Heating	A	4.0(1.02-5.32)	4.60(1.5-8.0)
	Max. Input Power		W	1600	1900
	Max. Input Current		A	9	9.5
	EER Cooling		W/W	(SEER) 7.5	3.21
	COP Heating		W/W	(SCOP) 4.2	3.62
	Power supply source		V/Ph/Hz	220-240V-1-50Hz	220-240V-1-50Hz
	Refrigerant			R32	R32
	Noise level		dB (A)	53	42/39/36/33
	Noise level		dB (A)	61	53/50/46/45
	Indoor unit weight (Net)		Kg	7.5	8
	Outdoor unit weight (Net)		Kg	23	22
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	774*298*202
		Packing Dimension(WidthxDepthxHeight)		mm	831*371*282
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	708*258*530
		Packing Dimension(WidthxDepthxHeight)		mm	825x345x595

AUX SPLIT ROOM AIR CONDITIONER			NUMBER	24K
Items				ASW-H24G3B4/CAR3DI
Nameplate Parameter	Rated Capacity	Cooling	W	7300 (1800-7400)
		Cooling	BTU	24000
		Heating	W	7300 (1800-7400)
		Heating	BTU	24000
	Rated Power Consumption	Cooling	W	2200 (230-2700)
		Heating	W	2200 (230-2530)
	Rated Running Current	Cooling	A	10 (1.0-12)
		Heating	A	10 (1.0-11)
	Max. Input Power			W
				3400
	Max. Input Current			A
				16
	EER Cooling			W/W
				(SEER)6.5
	COP Heating			W/W
				(SCOP)4.1
Indoor unit configuration	Power supply source			V/Ph/Hz
				220-240V~/50Hz
	Refrigerant			
				R32
Outdoor unit configuration	Noise level			dB (A)
				63
	Noise level			dB (A)
				66
Indoor unit weight (Net)			Kg	13
Outdoor unit weight (Net)			Kg	3
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm
		Packing Dimension(WidthxDepthxHeight)		mm
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm
		Packing Dimension(WidthxDepthxHeight)		mm

# C+PRO SERIES



Size:mm(12k)




▼ OUTDOOR UNIT

▼ REMOTE CONTROLLER



## APPEARANCE



## MAIN SELLING POINT

### LARGE COOLING CAPACITY

Air outlet: Wider and further, faster cooling and heating  
Air supply mode: Wide-angle air supply with large outlet brings the wind across the living room and dining room, providing a comfortable environment



### WIFI CONTROL

Develop the leading technology and intelligently connect with mobile phone, achieving remote control of the air conditioner



### SMART MICRO-PERFORATION WIND

Equipped with new micro-perforation air guide plate delivers lighter, softer, and more comfortable air supply in the guaranteed cool environment



## 8°C CONSTANT TEMPERATURE

Constant temperature heating, surrounded by comfortable breeze



## CHASSIS ELECTRICAL HEATING

Wide range of working environment temperature, startup at extremely low temperature



## CLEANING REMINDER

The dirt condition on filter screen could be displayed through light board to remind users of cleaning in time



## EASY INSTALLATION

Detachable underjaw and plate support for large operation space. The installation efficiency is greatly improved, saving 20% of installation time



## THE FIFTH GENERATION OF SELF-CLEANING

Comprehensive upgrade, six steps for cleaning indoor and outdoor units thoroughly. Remove four major bacteria with 99.9% sterilization rate



## FULL DC INVERTER COMPRESSOR

Start from -30°C low temperature to 60°C high temperature, not afraid of cold and heat. Low frequency operation and energy saving



# PRODUCT SPECIFICATION SHEET

AUX SPLIT ROOM AIR CONDITIONER			NUMBER	09K	12K
Items			ASW-H09B7A4/CAR3DI	ASW-H12C5A4/CAR3DI	
Rated Capacity	Cooling	W	2700 (600-4000)	3600 (800-4100)	
	Cooling	BTU	9000	12000	
	Heating	W	3200 (800-4200)	3800 (1000-4200)	
	Heating	BTU	9000	12000	
	Cooling	W	780 (100-1200)	1120(100-1600)	
	Heating	W	840 (200-1200)	1050(300-1600)	
	Cooling	A	3.7(0.56-5.32)	5.30(0.7-7.8)	
	Heating	A	4.0(1.02-5.32)	4.60(1.5-8.0)	
Nameplate Parameter	Max. Input Power			1600	1900
	Max. Input Current			9	9.5
	EER Cooling			(SEER) 7.5	3.21
	COP Heating			(SCOP) 4.2	3.62
	Power supply source			V/Ph/Hz	220-240V-1-50Hz
	Refrigerant			R32	R32
	Noise level			dB (A)	53
	Noise level			dB (A)	61
Dimension	Indoor unit weight (Net)			Kg	7.5
	Outdoor unit weight (Net)			Kg	23
	Net Dimension(WidthxDepthxHeight)			mm	774*298*202
	Packing Dimension(WidthxDepthxHeight)			mm	831*371*282
Dimension	Net Dimension(WidthxDepthxHeight)			mm	708*258*530
	Packing Dimension(WidthxDepthxHeight)			mm	825*345*595

# PRODUCT SPECIFICATION SHEET


AUX SPLIT ROOM AIR CONDITIONER			NUMBER	09K	12K
Items				ASW-H09B6A4/ FQA800R3DI-D0	ASW-H12C5A4/ FQAR3DI-D0
Nameplate Parameter	Rated Capacity	Cooling	W	2700(600-4000)	3500 (800-4100)
		Cooling	W	3300(800-4200)	3800 (1000-4200)
		Dehumidifying	Kg/h	1.0	/
	Rated Power Consumption	Cooling	W	640(100-1200)	900(100-1600)
		Heating	W	720(200-1200)	1050(300-1600)
	Rated Running Current	Cooling	A	3.2(0.56-5.32)	4.2(0.7-7.8)
		Heating	A	3.7(1.02-5.32)	4.8(1.5-8.0)
	SEER Cooling	W/W	9.0	8.8	
	SCOP Heating	W/W	4.7	4.7	
	Power supply source	V/Ph/Hz	220-240V~/50Hz	220-240V-1-50Hz	
Indoor unit configuration	Refrigerant	/	R32	R32	
	Noise level	dB (A)	54	54	
	Noise level	dB (A)	61	61	
	Indoor unit weight (Net)	Kg	9.5	9.5	
	Outdoor unit weight (Net)	Kg	24.5	24.5	
	Dimension	Net Dimension(WidthxDepthxHeight)	mm	890x311x212	35FQA-890*311*212
		Packing Dimension(WidthxDepthxHeight)	mm	960*382*300	960*382*300
	Dimension	Net Dimension(WidthxDepthxHeight)	mm	1.3PA-705x279x530	1.3PA-705x279x530
Outdoor unit configuration		Packing Dimension(WidthxDepthxHeight)	mm	825x345x595	825x345x595
	Container Loading 20/40/40HC	set	108/228/271	108/228/271	




# Q-SERIES



Size:mm(12k)



## APPEARANCE



■ Optional ■ Standard

	Hydrophilic Aluminium Fin		Self-Cleaning		Sleep Mode		Anti-Fungus Function		Anti-Cold-Air (Heat Pump Only)
	Self-diagnosis Function		Powerful Dehumidification		Super EMC performance		Anti-Rust Cabinet		Internal thread Copper Piping
	Timer		iFeel		iFavor		Golden Fin		Bio Filter
	Silver Ion Filter		Ionizer		Auto-Restart				

## MAIN SELLING POINT


### EASY MAINTENANCE

Modular design of core components, with the maintenance efficiency promoted by 50%.  
The main board of the indoor unit can be pulled out for quick disassembly and assembly.  
Optimized wiring mode of the outdoor unit, i.e. front wiring



## EFFICIENT STERILIZATION, MORE THAN JUST FILTRATION

New generation of super cleaning technology. Press start UVC with 99.9% sterilization rate. Six steps for cleaning indoor and outdoor units thoroughly. Purify inner AC in depth. Build a high-quality respiratory environment.



## NON-INDUCTIVE 1°C PRECISE CONTROL FOR YOUR SENSITIVITY

Super low frequency running at 1Hz with the control precision reaching 0.1Hz and energy saving exceeding 25%




## REMOVABLE SILVER-ION ANTIBACTERIAL FILTER

Dismantle within 1 second and easy to clean silver-ion added with sterilization and anti-fungus rate higher than 99%



## TRAVEL CONTENTEDLY IN COLD WINTER

8°C constant temperature heating provides a reliable living environment for the unattended animals and plants for a long time



# PRODUCT SPECIFICATION SHEET

AUX SPLIT ROOM AIR CONDITIONER			NUMBER	09K	12K
Items				ASW-H09B6A4/QCR1DI-C0	ASW-H12C4A4/QCR1DI-B6
Nameplate Parameter	Rated Capacity	Cooling	W	2600	3200
		Cooling	BTU	9000	12000
		Heating	W	2640	3400
		Heating	BTU	9000	12000
	Rated Power Consumption	Cooling	W	880	1350
		Heating	W	700	900
	Rated Running Current	Cooling	A	4.1	6.0
		Heating	A	3.44	4.0
	Max. Input Power		W	1400	1600
	Max. Input Current		A	7.0	8.5
	EER Cooling		W/W	2.95	2.37
	COP Heating		W/W	3.77	3.78
	Power supply source		V/Ph/Hz	220-240V~/50Hz	220-240V~/50Hz
	Refrigerant			R410A	R410A
	Noise level		dB (A)	40	43
	Noise level		dB (A)	53	53
	Indoor unit weight (Net)		Kg	7	8.5
	Outdoor unit weight (Net)		Kg	18	18
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	708*282*193
		Packing Dimension(WidthxDepthxHeight)		mm	765*351*269
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	650*455*278
		Packing Dimension(WidthxDepthxHeight)		mm	760*510*315

AUX SPLIT ROOM AIR CONDITIONER			NUMBER	18K	24K
Items				ASW-H18D7A4/QCR1DI-B9	ASW-H24F0A4/QCR1DI-C2
Nameplate Parameter	Rated Capacity	Cooling	W	5100	6000
		Cooling	BTU	18000	24000
		Heating	W	5100	6300
		Heating	BTU	18000	24000
	Rated Power Consumption	Cooling	W	1750	2190
		Heating	W	1410	2030
	Rated Running Current	Cooling	A	7.9	9.5
		Heating	A	6.2	8.8
	Max. Input Power		W	2300	3000
	Max. Input Current		A	12	13
	EER Cooling		W/W	2.91	2.74
	COP Heating		W/W	3.62	3.10
	Power supply source		V/Ph/Hz	220-240V~/50Hz	220~240V/1/50Hz
	Refrigerant			R410A	R410A
	Noise level		dB (A)	44	48
	Noise level		dB (A)	54	56
	Indoor unit weight (Net)		Kg	8.5	10.5
	Outdoor unit weight (Net)		Kg	26	28
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	816*295*200
		Packing Dimension(WidthxDepthxHeight)		mm	885*367*277
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	785*300*555
		Packing Dimension(WidthxDepthxHeight)		mm	888*367*590

# F-SERIES



## APPEARANCE



■ Optional ■ Standard

- Hydrophilic Aluminium Fin
- Self-Cleaning
- Sleep Mode
- Anti-Fungus Function
- Anti-Cold-Air (Heat Pump Only)
- Self-diagnosis Function
- Powerful Dehumidification
- Super EMC performance
- Anti-Rust Cabinet
- Internal thread Copper Piping
- Timer
- iFeel
- iFavor
- Golden Fin
- Silver Ion Filter
- Ionizer
- Auto-Restart
- Bio Filter

# MAIN SELLING POINT

## REMOTE AIR SUPPLY

Remote air supply (9K, 12K/10m, 18K and above/15m), fish-fin air guide blades (not available on F model) for wider and farther air delivery



## FIFTH-GENERATION AUTOMATIC CLEANING

Newly upgraded, 6-step water washing more thoroughly, in addition to the 4 major germs, the sterilization rate of 99.9%



## EASY INSTALLATION

Detachable underjaw and plate support for large operation space. The installation efficiency is greatly improved, Save 20% of installation time, installing workers reduced to 1 person



## FAST COOLING AND HEATING (INVERTER ONLY)

30s fast cooling, 60s fast heating  
One step faster in heating and cooling



# PRODUCT SPECIFICATION SHEET

AUX SPLIT ROOM AIR CONDITIONER			NUMBER	09K	12K
Items				ASW-H09B1B4/FAR1-B2	ASW-H12C0D4/FAR1-B4
Nameplate Parameter	Rated Capacity	Cooling	W	2800	3000
		Cooling	BTU	9000	12000
		Heating	W	2900	3200
		Heating	BTU	9000	12000
	Rated Power Consumption	Cooling	W	860	1250
		Heating	W	800	1060
	Rated Running Current	Cooling	A	4.8	6
		Heating	A	4.5	5.6
	Max. Input Power		W	1300	1650
	Max. Input Current		A	6.2	8
	EER Cooling		W/W	3.26	2.4
	COP Heating		W/W	3.63	3.02
	Power supply source		V/Ph/Hz	220-240V~/50Hz	220-240V~/50Hz
	Refrigerant			R410A	R410A
	Noise level		dB (A)	38	44
	Noise level		dB (A)	51	52
	Indoor unit weight (Net)		Kg	7.5	8
	Outdoor unit weight (Net)		Kg	22.5	24.5
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	690*283*199
		Packing Dimension(WidthxDepthxHeight)		mm	760*347*277
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	727*456*278
		Packing Dimension(WidthxDepthxHeight)		mm	760*510*305


AUX SPLIT ROOM AIR CONDITIONER			NUMBER	18K	24K
Items				ASW-H18D2C4/FAR1-B6	ASW-H24F0A4/FAR1-C2
Nameplate Parameter	Rated Capacity	Cooling	W	4600	6050
		Cooling	BTU	18000	24000
		Heating	W	4800	6400
		Heating	BTU	18000	24000
	Rated Power Consumption	Cooling	W	1850	1990
		Heating	W	1700	1970
	Rated Running Current	Cooling	A	8.8	9.50
		Heating	A	8.1	9
	Max. Input Power		W	/	/
	Max. Input Current		A	11	14
	EER Cooling		W/W	2.49	3.04
	COP Heating		W/W	2.82	3.25
	Power supply source		V/Ph/Hz	220-240/50	220-240V/50Hz
	Refrigerant			R410A	R410A
	Noise level		dB (A)	43	47
	Noise level		dB (A)	55	58
	Indoor unit weight (Net)		Kg	9.5	11.5
	Outdoor unit weight (Net)		Kg	34	45
Indoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	900*310*225
		Packing Dimension(WidthxDepthxHeight)		mm	970*382*302(50FA)
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)		mm	800*545*315
		Packing Dimension(WidthxDepthxHeight)		mm	920*620*400

# PORTABLE



## SUPER QUIET

Through the air tunnel optimization technology and equipped with big diameter fan and high efficiency PG motor, which help the indoor unit deliver a better air distribution and air flow with noise low to 45dB, providing you comfortable sleeping environment



## LONG-DISTANCE REMOTE CONTROL

Effective remote-control distance of 10 meters makes it more convenient



## SILENCER COTTON, DUAL-LAYER

Reduce the noise level from compressor by decreasing vibration of the whole unit



## ADVANTAGE WATER ATOMIZATION

Without water tank, automatically fetching water to the condenser, make water evaporate

Reduce the condensing temperature, reduce power consumption, enhancing the condensation efficiency



## SOUND INSULATION COTTON WITH LARGE AREA

Effectively suppress the noise of compressor operation, improve the comfort level and it will not disturb your rest.



## LARGE DISPLAY SCREEN

Large touch panel together with easy operation



# PRODUCT SPECIFICATION SHEET

AUX SPLIT ROOM AIR CONDITIONER		NUMBER	12K
Items			AM-H12C2A4/MAR1-BO
Rated Capacity	Cooling	W	3000
	Cooling	BTU	12000
	Heating	W	3000
	Heating	BTU	12000
Rated Power Consumption	Cooling	W	1700
	Heating	W	1400
Rated Running Current	Cooling	A	7.1
	Heating	A	7.1
Max. Input Power		W	2400
Max. Input Current		A	10
Nameplate Parameter	EER Cooling	W/W	1.7
	COP Heating	W/W	2.1
	Power supply source	V/Ph/Hz	220-240V/1/50Hz
	Refrigerant		R410A
	Noise level	dB (A)	53
	Noise level	dB (A)	/
	Indoor unit weight (Net)	Kg	30
	Outdoor unit weight (Net)	Kg	/
	Dimension	Net Dimension(WidthxDepthxHeight)	mm
		Packing Dimension(WidthxDepthxHeight)	mm
Outdoor unit configuration	Dimension	Net Dimension(WidthxDepthxHeight)	mm
		Packing Dimension(WidthxDepthxHeight)	mm

