



# Cassette



■ optional ■ standard

## FEATURES



Remote Control



Built-in Drain Pump



Auto Restart Function



Digital Tube Display



Sleep Mode



Independent Dehumidification



Silent



Anti-Cold-Air



Self-diagnosis Function



Low Ambient Cooling



Long-term Filter



Intelligent Defrosting



Wired Control



Central Control



Golden Fin



WIFI Control

# Feature

## ► 5-fold exchanger

The evaporator adopts a 5-fold evaporator, which has a larger heat exchange area



## ► Round-way air supply

Round flow panel make the air diffuse from 360° direction, and the temperature distribution is more uniform



## ► Big air volume

Adopting a large-diameter spiral wind wheel for larger air volume and lower noise




## ► long distance air supply

Long air supply distance, meeting the air supply requirements for tall spaces




## ► Sleeping mode

Turn on sleep mode at night, no need to worry about being too cold or too hot, and sleep comfortably all night long



## ► Central control function

Optional dry node function, when the unit senses the window opening or sensing the fire, the unit will automatically shut down



# Feature

## ▶ Screen display function

When the unit is running, the light panel icon can be set to display or not to display to meet the needs of different customers



## ▶ Auto clean

Automatic cleaning of evaporator, cleaning of dust and dirt, healthy and comfortable




## ▶ Fresh air

And long-term use will not cause dizziness, healthy and comfortable



## ▶ Anti-leakage water pan

Using 1.5mm thick plastic drain pan, with high waterproof performance and effective prevention of water seepage



# Feature

## ► Fire-proof covercover

The fireproof electric control box made of metal materials has higher safety, ensuring the safe operation of the unit




## ► Reliable control board

Hot melt adhesive is applied around the electronic components to keep the components stable



## ► Compact body size

The thickness of the body is 246mm, occupying less ceiling space and making installation more convenient



## ► Removable grille

No need for tools, just press lightly to open the grille, making installation more convenient



## ► Wifi room card

Optional WiFi, reserved room card port, and centralized control functions to meet intelligent needs



# R32 Standard Efficiency DC Inverter Series

## Cassette Specification



Model	Indoor		ALCA-H12/4DR3AA-R	ALCA-H18/4DR3AA-R	ALCA-H24/4DR3AA-R	
	Outdoor		AL-H12/4DR3A-R	AL-H18/4DR3A-R	AL-H24/4DR3A-R	
IDU Power Supply			V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	Btu/h	12000(3500~12750)	18000 (5200~19100)	24000 (7400~25590)	
		KW	3.52(0.60~3.90)	5.30 (1.53~5.61)	7.03 (2.16~7.50)	
Capacity	Heating	Btu/h	13650(2400~14330)	19100 (4800~20300)	25590 (6755~25930)	
		KW	4.00(0.60~4.20)	5.60 (1.40~5.94)	7.60 (1.98~7.90)	
Electric Data	Rated Cooling Power Input		KW	1.07(0.30~1.50)	1.60 (0.47~1.90)	2.15 (0.67~2.40)
	Rated Heating Power Input		KW	1.08(0.25~1.45)	1.40 (0.46~1.90)	1.90 (0.65~2.65)
	Rated Cooling Current		A	6.20(1.30~7.50)	7.50 (2.25~8.40)	10.30 (3.21~11.00)
	Rated Heating Current		A	6.20(1.10~7.00)	6.50 (2.20~8.40)	9.00 (3.11~10.00)
Performance	EER		W/W	3.30	3.31	3.27
	COP		W/W	3.70	4.00	4.00
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)		m <sup>3</sup> /h	850/700/650	900/750/650	1400/1250/850
	Noise Level(Hi/Mi/Lo)		dB(A)	44/41/38	45/42/39	46/43/39
	Net Dimension (W*H*D)		mm	570×570×260	570×570×260	840×840×246
	Packing Dimension (W*H*D)		mm	720×650×290	720×650×290	910×910×310
	Net Weight		Kg	14.5	15	25
	Gross Weight		Kg	17.5	18	29
Panel	Net Dimension (W*H*D)		mm	650×650×55	650×650×55	950×950×55
	Packing Dimension (W*H*D)		mm	710×710×80	710×710×80	1000×1000×100
	Net weight		Kg	2.2	2.2	5.7
	Gross weight		Kg	3.7	3.7	7.8
Refrigerant Pipe	Liquid Side		mm	6.35(1/4)	6.35(1/4)	9.52(3/8)
	Gas Side		mm	9.52(3/8)	12.7(1/2)	15.88(5/8)
	Drainage		mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range			°C	16~32	16~32	16~32
Wireless Remote Controller				YKR-H/009E	YKR-H/009E	YKR-H/009E

Model	Indoor		ALCA-H36/4DR3AA-R	ALCA-H48/5DR3AA-R	ALCA-H60/5DR3AA-R	
	Outdoor		AL-H36/4DR3A-R	AL-H48/5DR3A-R	AL-H60/5DR3A-R	
IDU Power Supply			V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	Btu/h	36000(12280~37530)	48000 (14330~49540)	55000 (16400~57320)	
		KW	10.55(3.60~11.00)	14.07(4.20~14.52)	16.12 (4.80~16.80)	
Capacity	Heating	Btu/h	39880(9210~40940)	52000 (15700~58000)	60050 (16700~62780)	
		KW	11.7(2.70~12.00)	15.24(4.60~17.00)	17.60 (4.90~18.40)	
Electric Data	Rated Cooling Power Input		KW	3.40 (0.42~3.80)	4.67 (1.21~6.30)	5.36 (1.38~6.80)
	Rated Heating Power Input		KW	3.08 (0.80~3.35)	4.22(0.92~5.80)	5.16 (0.98~6.00)
	Rated Cooling Current		KW	15.20(1.82~17.80)	10.00(2.50~11.00)	10.50 (2.85~11.50)
	Rated Heating Current		A	13.40(3.40~14.60)	8.00(1.90~8.50)	9.50 (2.02~10.00)
Performance	EER		A	3.10	3.01	3.01
	COP		W/W	3.80	3.61	3.41
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)		W/W	1800/1450/1250	1900/1500/1300	1900/1500/1300
	Noise Level(Hi/Mi/Lo)		m <sup>3</sup> /h	51/46/42	51/46/42	51/46/42
	Net Dimension (W*H*D)		dB(A)	840×840×246	840×840×288	840×840×288
	Packing Dimension (W*H*D)		mm	910×910×310	915×915×355	915×915×355
	Net Weight		Kg	25	28	28
	Gross Weight		Kg	29	32	32
Panel	Net Dimension (W*H*D)		mm	950×950×55	950×950×55	950×950×55
	Packing Dimension (W*H*D)		mm	1000×1000×100	1000×1000×100	1000×1000×100
	Net weight		Kg	5.7	5.7	5.7
	Gross weight		Kg	7.8	7.8	7.8
Refrigerant Pipe	Liquid Side		mm	9.52(3/8)	9.52(3/8)	9.52(3/8)
	Gas Side		mm	15.88(5/8)	15.88(5/8)	15.88(5/8)
	Drainage		mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range			°C	16~32	16~32	16~32
Wireless Remote Controller				YKR-H/009E	YKR-H/009E	YKR-H/009E

Remarks:

- 1.Data from AUX lab, Data may change according to test surroundings, AUX reserves right of explanation on data
- 2.All specifications are subject to change by the manufacturer without prior notice